

Bondit™

COLOR: Clear

- BASIC USES:**
- Effective bleed-through blocker over bitumen
 - Adhesive enhancer

PRODUCT DESCRIPTION: Bondit allows for instant compatibility of Topps Seal® solvent based products over stable black bituminous systems for resurfacing them with rubber durability and the Topps Seal Energy Star® protective layer. Its tenacious adhesive bond to asphalt bitumen on the bottom side also becomes a barrier to asphalt to prevent discoloring the finish coat. The strong chemical affinity of Bondit to Topps Seal on the top is inseparable, making the system complete. Bondit dries in as little as 2 hours for quick project completion.

- FEATURES:**
- A package that doubles for enhanced adhesion to bitumen and final finish color development

WET MATERIAL

Typical Product Characteristics:

Color	Milky/Clear
Viscosity	Water Thin
Weight per gallon	9.0 - 10.0 lb.
Solids	36.5% min.
pH	<8.5
VOC	0 g/l
Dry to touch @ 77° F (50% rel. humidity)	2 hrs

CURED COATING

Typical Performance Properties:

Coverage Rate	1 gal/100 ft ²
Ultimate Elongation	750%
Ultimate tensile strength	500 psi
Tg	32° F

Water based – do not allow to freeze